

KS10C / KS12C / KS208 / KS210

KS Series Entertainment Speaker



Characteristic:

- Applications: Karaoke System, Club, Entertainment Venues, KTV rooms, Bars etc.
- KS10C and KS12C is a two-way full-range audio, the speaker adopts a low-frequency reflective design, which can produce a sense of great envelopment of the low frequency, round and thick midrange, clear and delicate high frequency, microphone sound real natural and highly infectious, suitable for a variety of entertainment venues;
- Ks208 and KS210 is a three-way full-range audio, KS208 is composed of two 8" foam LF drivers and two 3" paper cone mid-range drivers as well as two 3" silk film HF drivers, KS210 is composed of two 10" foam LF drivers and two 3" paper cone mid-range drivers as well as two 3" paper cone HF drivers.
- Both of the two models feature rich and extended bass, mellow mid-range, as well as remarkable and vigorous vocal passed through microphone. The elegant enclosure designed with multi-point and multi-angle suspension is convenient to fast installation.

Specifications:

Model	KS10C	KS12C	KS208	KS210
Frequency Response	50Hz-20KHz	45Hz-20KHz	40Hz-18KHZ	35Hz-18KHz
Sensitivity(1 W@1m)	97dB	98dB	95dB	98dB
Nominal Impedance	8Ω	8Ω	4Ω	4Ω
Rated Power	300W AES, 1200W peak	400W AES, 1800W peak	300W AES, 1400W peak	450W AES, 1800W peak
LF Driver	300W AES, 1200W peak	400W AES, 1800W peak	300W AES, 1400W peak	450W AES, 1800W peak
MF Driver	1x10(250mm)/2.5" voice coil	1x12(300mm)/3" voice coil	2x8"(200mm)/ woofer	2x10"(250mm) Woofer
HF Driver			2x3"(75mm) voice coil MF	2x3"(75mm) voice coil MF
Dispersion	80°×70°	80°×70°		
Maximum SPL	121dB continuous, 127dB peak	123dB continuous, 129dB peak	115dB continuous, 121 dB peak	123dB continuous, 129dB peak
Connectors	2 x Speakon NL4			
Net Weight	13 kg	13 kg	13 kg	13 kg
Dimensions(WxDxH)	300×340×530 (mm)	300×340×530 (mm)	300×340×530 (mm)	300×340×530 (mm)

